Analysis and Evaluation of Continuous Speech by Simultaneous Spotting of Phonemes, Words and Phrases

Yasuo ARIKI and Mitsuyasu SAKURAI
Department of Electronics and Informatics,
Faculty of Science and Engineering,
Ryukoku University, Seta, Otsu, Shiga, Japan 520-21
e-mail: ariki@rins.ryukoku.ac.jp

1. Introduction

In human speech recognition, we can discriminate known words and unknown words contained in natural speech. This indicates following two points. Firstly we can easily locate or spot important known words and then understand the sentence meaning by skipping unknown words. Secondly we can also learn phoneme sequence of unknown words from their utterances and sometimes learn their meaning from the context.

This word spotting function seems to be effective even in a man-machine dialogue system, because human speech is not so rigid nor complete as it can be analyzed computationally by natural language grammar. The purpose of this paper is to clarify techniques to discriminate known words from unknown words in natural speech without using any language grammar. Here, four word spotting methods are theoretically and experimentally compared; forward-backward, heuristic Viterbi and their simplified methods.

2. Theoretical comparison

2.1 Probability ratio method

Known words have the constraints on a sequence of phonemes included in them. If x is utterance of a known word w, the probability $P(x|p^*_{seq})$, where p_{seq} is any phoneme sequence and p^*_{seq} is the best fit phoneme sequence to the utterance x, will be almost same as the probability $P(x|w)$, because the phoneme sequence of the known word w will be almost same as the best fit phoneme sequence p^*_{seq}. Then probability ratio $P(x|w)/\ P(x|p^*_{seq})$ almost equals unit.

On the other hand, if the utterance x is unknown word, any probabilities $P(x|w)$ will be far from that of the best fit phoneme sequence. Therefore the probability ratio $P(x|w)/P(x|p^*_{seq})$ will be less than some threshold θ for unknown words. We call this method *probability ratio method.*

2.2 Forward-backward probability method

Probability ratio can be expressed as follows under the assumption of $P(w) = P(p_{seq})$;

$$\begin{aligned}\frac{P(x|w)}{P(x|p^*_{seq})} &= \frac{P(x|w)P(w)}{P(x|p^*_{seq})P(p^*_{seq})} \\ &= \frac{P(x,w)}{P(x,p^*_{seq})}\end{aligned}$$

$$= \frac{P(x,w)}{\max\limits_{p_{seq}} P(x,p_{seq})}$$

If we sum the phoneme sequence probabilities, instead of selecting the best fit phoneme sequence, the probability ratio can be regarded as a posteriori probability as shown in the following expression [1];

$$\begin{aligned} \frac{P(x,w)}{\max\limits_{p_{seq}} P(x,p_{seq})} &= \frac{P(x,w)}{\sum\limits_{p_{seq}} P(x,p_{seq})} \\ &= P(w|x) \end{aligned}$$

If the input utterance x is continuous speech, *a posteriori probability* of each $word_i$ is computed at every time t as follows;

$$\begin{aligned} \gamma_t & \ (word_i\_last\_state) \\ = & \ P(s_t = word_i\_last\_state|x) \\ = & \ \frac{\alpha_t(word_i\_last\_state)\beta_t(word_i\_last\_state)}{\sum\limits_{alls} \alpha(s)\beta(s)} \end{aligned}$$

where $\alpha_t(s)$ and $\beta_t(s)$ are the forward and backward probabilities respectively. If a posteriori probability shows local peaks, known words are located at the peaks. We call this method forward-backward method. (Fig.1) shows the topology of the word and phoneme occurrence in a forward-backward method.

2.3 Viterbi method

This approach can be formalized using Viterbi decoding in 2.2, instead of forward-backward computation. Namely, the best path ending with $word_i$ at time t is searched by Viterbi decoding and its accumulated probability is computed. This probability corresponds to $\alpha_t(word_i\_last\_state)$ in expression(3). In general, the best path just before $word_i$ will be a phoneme sequence as shown in (Fig.2), because phoneme sequence has heigher probability than word sequence.

In the same way, after $word_i$, the best path will be a phoneme sequence. This accumulated probability of this best path corresponds to $\beta_t(word_i\_last\_state)$ in expression(3). Therefore, the topology shown in (Fig.3) is obtained from Fig.1.

The Viterbi decoding contributes to find the best ending time of $word_i$.[2] This approach basically spots one word by Viterbi decoding. To catch more than one word on utterance, N best words are searched by changing the $word_i$ in the topology. We call this method Viterbi method.

This method computes a likelihood $f(w, t_1, t_2)$ that a word w locates between time t_1 and t_2 in spoken sentence as follows

$$f(w,t_1,t_2) = g(w,t_1,t_2) + h(w,t_1,t_2)$$